

# FlexIT JF10K

TWO WIRE BRAID COMPACT HOSE

## HIGH PRESSURE FOR JACK APPLICATIONS



### Construction

- 1 - Synthetic rubber tube;
- 2 - Two high tensile steel wire braids;
- 3 - Synthetic rubber cover, MSHA flame retardant approved;

### Application



Hydraulic oils, both mineral and biological; polyglycol base oils, water-oil emulsions, water.

### Temperature range

-40°C to +100°C (-40°F to +212°F);

HOSE TYPE	Ø HOSE			REINFORCEMENT DIAMETER		MAX OUTSIDE DIAMETER		WORKING PRESSURE		BURST PRESSURE		BEND RADIUS		WEIGHT	
	DN	INCH	SIZE	[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[mm]	[in]	[kg/m]	[lb/ft]
JF10K-04	6	1/4"	04	11,5	0,453	13,8	0,543	700	10000	1400	20000	45	1,77	0,27	0,18
JF10K-06	10	3/8"	06	15,0	0,591	17,5	0,689	700	10000	1400	20000	70	2,76	0,39	0,26

### COMPATIBILITY CHART BETWEEN THIS HOSE AND INTERTRACO APPROVED FITTINGS\*

FlexIT JF10K	-03	-04	-06	-08	-10	-12	-16	-20	-24	-32
1 Piece 		No-skive: <b>K</b> series								
2 Piece 		No-skive: <b>B</b> insert + <b>SN03T</b> ferrule								

\* For fittings details please make reference to Intertraco fittings catalogues.

\*\* Please refer to our crimping chart for more detailed application data.