



Long length antistatic oil hose for transfer and delivery of mineral oils, greases and petroleum based products up to a maximum aromatic content of 50%. The liner is electrically conductive: $R < 106 \text{ Ohm/m}$ (ISO 8031:2009). The cover is isolating $R > 109 \text{ Ohm/m}$.

- Application: **Oil / Grease / Universal**
- Standard Length: **50 metres**
- Working Temperature: **-25°C to 100°C**
- Inside: **NBR**
- Colour: **Black**
- Reinforcement: **PVA**
- Outside: **NBR/PVC**
- Colour: **Black**

Inside dia. (mm)	DN size	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,0	1/4"	14,0	25	75	60	190	3012006000
8,0	5/16"	16,0	25	75	80	220	3012008000
10,0	3/8"	18,0	25	75	100	251	3012010000
13,0	1/2"	18,0	25	75	120	352	3012013000
16,0	5/8"	25,0	25	75	150	415	3012016000
19,0	3/4"	29,0	25	75	180	593	3012019000
25,0	1"	36,0	25	75	240	785	3012025000
32,0	1.1/4"	44,0	20	60	320	1.130	3012032000
38,0	1.1/2"	51,0	20	60	380	1.470	3012038000
50,0	2"	65,0	20	60	500	2.190	3012050000