


Straight Fitting with 24° Taper / O-Ring Type FI-SNV • Series L / S



Ordering Codes

FI-SNV-10*L*-B*-W3*-DKO

* Straight Fitting with 24° Taper / O-Ring (DKO)	FI-SNV
* Outside Tube Diameter D1 (in mm)	-10
* Series	Light Series L Heavy Series S
* Seal Material	NBR (Buna-N®) -B FKM/FPM (Viton®) -V EPDM -E
* Material Code	Steel, zinc/nickel-plated -W3
Please contact STAUFF for alternative materials and surface finishings.	
* Assembling / Kitting	Fitting body supplied with swivel nuts and O-rings -DKO

Spare Parts / Accessories



O-Ring
Type **O-RING**

Page 207

Series	Tube OD (mm/in) D1	PN (bar/psi)	Dimensions (mm/in) D2 L1 L2 S1				Weight (kg/lbs) ca. per 100	Ordering Codes
L	6	500	3	34	36,7	14	3,82	FI-SNV-06L-B-W3-DKO
	.24	7250	.12	1.34	1.44	.55	8.40	
	8	500	5	34	36,7	17	4,29	FI-SNV-08L-B-W3-DKO
	.31	7250	.20	1.34	1.44	.67	9.44	
	10	500	6	36	37,8	19	5,78	FI-SNV-10L-B-W3-DKO
	.39	7250	.24	1.42	1.49	.75	12.72	
	12	400	8	36	37,8	22	7,00	FI-SNV-12L-B-W3-DKO
	.47	5800	.31	1.42	1.49	.87	15.40	
	15	400	11	39	40,8	27	12,58	FI-SNV-15L-B-W3-DKO
	.59	5800	.43	1.54	1.61	1.06	27.68	
	18	400	13	40,5	43,3	32	17,59	FI-SNV-18L-B-W3-DKO
	.71	5800	.51	1.59	1.70	1.26	38.70	
	22	250	17	45	47,8	36	24,91	FI-SNV-22L-B-W3-DKO
	.87	3625	.67	1.77	1.88	1.42	54.80	
	28	250	23	46	48,8	41	27,40	FI-SNV-28L-B-W3-DKO
	1.10	3625	.91	1.81	1.92	1.61	60.28	
	35	250	28	53	59	50	45,98	FI-SNV-35L-B-W3-DKO
	1.38	3625	1.10	2.09	2.32	1.97	101.15	
	42	250	35	53	60	60	69,50	FI-SNV-42L-B-W3-DKO
	1.65	3625	1.38	2.09	2.36	2.36	152.90	
S	6	800	3	37	39,7	17	4,52	FI-SNV-06S-B-W3-DKO
	.24	11600	.12	1.46	1.56	.67	9.95	
	8	800	4	37	39,7	19	6,03	FI-SNV-08S-B-W3-DKO
	.31	11600	.16	1.46	1.56	.75	13.27	
	10	800	6	41	43,8	22	8,39	FI-SNV-10S-B-W3-DKO
	.39	11600	.24	1.61	1.72	.87	18.47	
	12	630	8	42	44,8	24	10,51	FI-SNV-12S-B-W3-DKO
	.47	9135	.31	1.65	1.76	.94	23.13	
	14	630	9	45	48,8	27	13,90	FI-SNV-14S-B-W3-DKO
	.55	9135	.35	1.77	1.92	1.06	30.59	
	16	630	10	46	50,8	30	17,57	FI-SNV-16S-B-W3-DKO
	.63	9135	.39	1.81	2.00	1.18	38.66	
	20	400	13	55	61	36	24,36	FI-SNV-20S-B-W3-DKO
	.79	5800	.51	2.17	2.40	1.42	53.59	
	25	400	18	58	67	46	49,45	FI-SNV-25S-B-W3-DKO
	.98	5800	.71	2.28	2.64	1.81	108.79	
	30	400	20	62	74	50	61,40	FI-SNV-30S-B-W3-DKO
	1.18	5800	.79	2.44	2.91	1.97	135.08	
	38	400	30	67	84	60	86,70	FI-SNV-38S-B-W3-DKO
	1.50	5800	1.18	2.64	3.31	2.36	190.74	

Standard seal material is NBR (Buna-N®).

