



Blanking Plug for Tube Ends Type FI-VSK ■ Series L / S



Ordering Codes

FI-VSK-10*L*-W3*-MS

* Blanking Plug for Tube Ends	FI-VSK
* Outside Tube Diameter D1 (in mm)	-10
* Series	Light Series L Heavy Series S
* Material Code	Steel, zinc/nickel-plated -W3
Please contact STAUFF for alternative materials and surface finishings.	
* Assembling / Kitting	Blanking plug only —
	Blanking plug supplied with cutting ring and union nut -MS
	Blanking plug supplied with soft-sealing cutting ring and union nut -MSV

Connecting Parts

	Cutting Ring Type FI-DS	Page 26
	Soft-Sealing Cutting Ring Type FI-WDDS	Page 27
	Support Sleeve Type FI-VH	Page 28
	STAUFF Form Ring Type FI-AR	Page 30
	Union Nut Type FI-M	Page 31
	37° Flared Tube Fitting Set Type FI-AB	Page 35

Series	Tube OD (mm/in) D1	PN (bar/psi)	Dimensions (mm/in) L L1 ¹ L2 S1 S2					Weight (kg/lbs) ca. per 100 ²	Ordering Codes ³
L	6	315	14	22	7	12	14	1,40	FI-VSK-06L-W3
	.24	4568	.55	.87	.28	.47	.55	3,08	FI-VSK-08L-W3
	8	315	15	23	8	14	17	1,93	FI-VSK-10L-W3
	.31	4568	.59	.91	.31	.55	.67	4,24	FI-VSK-12L-W3
	10	315	16	24	9	17	19	2,55	FI-VSK-15L-W3
	.39	4568	.63	.94	.35	.67	.75	5,61	FI-VSK-18L-W3
	12	315	17	25	10	19	22	3,44	FI-VSK-22L-W3
	.47	4568	.67	.98	.39	.75	.87	8,74	FI-VSK-28L-W3
	15	315	18	26	11	24	27	4,90	FI-VSK-35L-W3
	.59	4568	.71	1.02	.43	.94	1.06	10,78	FI-VSK-42L-W3
	18	315	19	28	11,5	27	32	6,80	FI-VSK-22L-W3
	.71	4568	.75	1.10	.45	1.06	1.26	14,96	FI-VSK-28L-W3
	22	160	21	30	13,5	32	36	10,70	FI-VSK-35L-W3
	.87	2320	.83	1.18	.53	1.26	1.42	23,54	FI-VSK-42L-W3
	28	160	22	31	14,5	41	41	15,20	FI-VSK-06S-W3
	1.10	2320	.87	1.22	.57	1.61	1.61	33,44	FI-VSK-08S-W3
	35	160	25	36	14,5	46	50	25,90	FI-VSK-10S-W3
	1.38	2320	.98	1.42	.57	1.81	1.97	56,98	FI-VSK-12S-W3
	42	160	27	39	16	55	60	35,30	FI-VSK-14S-W3
	1.65	2320	1.06	1.54	.63	2.17	2.36	77,66	FI-VSK-16S-W3
S	6	630	18	26	11	14	17	1,80	FI-VSK-20S-W3
	.24	9135	.71	1.02	.43	.55	.67	3,96	FI-VSK-25S-W3
	8	630	20	28	13	17	19	2,16	FI-VSK-30S-W3
	.31	9135	.79	1.10	.51	.67	.75	4,75	FI-VSK-38S-W3
	10	630	20	29	12,5	19	22	3,34	FI-VSK-06S-W3
	.39	9135	.79	1.14	.49	.75	.87	7,35	FI-VSK-08S-W3
	12	630	22	31	14,5	22	24	4,60	FI-VSK-10S-W3
	.47	9135	.87	1.22	.57	.87	.94	10,12	FI-VSK-12S-W3
	14	630	24	34	16	24	27	5,88	FI-VSK-14S-W3
	.55	9135	.94	1.34	.63	.94	1.06	12,94	FI-VSK-16S-W3
	16	400	24	34	15,5	27	30	7,54	FI-VSK-20S-W3
	.63	5800	.94	1.34	.61	1.06	1.18	16,59	FI-VSK-25S-W3
	20	400	28	39	17,5	32	36	12,50	FI-VSK-30S-W3
	.79	5800	1.10	1.54	.69	1.26	1.42	27,50	FI-VSK-38S-W3
	25	400	32	44	20	41	46	21,40	FI-VSK-06S-W3
	.98	5800	1.26	1.73	.79	1.61	1.81	47,08	FI-VSK-08S-W3
	30	400	34	47	20,5	46	50	30,40	FI-VSK-10S-W3
	1.18	5800	1.34	1.85	.81	1.81	1.97	76,20	FI-VSK-12S-W3
	38	315	39	54	23	55	60	40,80	FI-VSK-14S-W3
	1.50	4568	1.54	2.13	.91	2.17	2.36	89,76	FI-VSK-16S-W3

¹ Approximate dimension in assembled condition.

² Weight excluding cutting ring and union nut.

³ Standard scope of delivery: Blanking plug only.

