



Clamp Body ■ Profiled Design

Profiled Inside Surface with Tension Clearance



STAUFF Group 1



STAUFF Group 1A to 8

Ordering Codes

Clamp Body

Clamp Body, STAUFF Group 1A

*1*06-*PP

*1*06A-*PP

One clamp body is consisting of two clamp halves.

* STAUFF Group

1

* Exact outside diameter Ø D1 (mm)

06

* Material code (see below)

PP

Standard Materials



Polypropylene

Colour: Green

Material code: PP



Polypropylene

Colour: Black

Material code: PP-BK



Polyamide

Colour: Black

Material code: PA



Thermoplastic Elastomer (87 Shore-A)

Colour: Black

Material code: SA



Aluminium

Colour: Self-Colour

Material code: AL (STAUFF Group 1A to 6)

See pages 154 / 155 for material properties and technical information.

Special Materials

Please contact STAUFF for further details on fire-proof clamp body materials, tested and approved according to several international fire-protection standards (such as BS 6853, EN 45545-2, UL 94 and many more).

See pages 156 / 157 for material properties and technical information.

Product Features

- Proven, tested and trusted product in various markets
- Recommended for the safe installation of rigid pipes and tubes
- Available for all commonly used pipe and tube outside diameters
- Environmental protection due to vibration/noise reducing design
- Excellent weathering resistance, even under extreme conditions

Group	STAUFF	DIN	Outside Diameter Pipe / Tube Ø D1		Nominal Bore Pipe (in)	Copper Tube ASTM B88 (in)	Ordering Codes (2 Clamp Halves) (** = Material)	Dimensions (mm/in)				
			(mm)	(in)				L1	L2	H	S min.	Width
1	0		6				106-***					
			6,4	1/4			106.4-***					
			8	5/16			108-***	28	9,5	27	0,4	30
			9,5	3/8		1/4	109.5-***	1.10	.37	1.06	.02	1.18
			10		1/8		110-***					
			12				112-***					
1A	1		6				106A-***					
			6,4	1/4			106.4A-***					
			8	5/16			108A-***	37	20	27	0,4	30
			9,5	3/8		1/4	109.5A-***	1.46	.79	1.06	.02	1.18
			10		1/8		110A-***					
			12				112A-***					
2	2		12,7	1/2		3/8	212.7-***					
			13,5		1/4		213.5-***					
			14				214-***	42	26	33	0,6	30
			15				215-***	1.65	1.02	1.30	.02	1.18
			16	5/8		1/2	216-***					
			17,2		3/8		217.2-***					
3	3		18				218-***					
			19	3/4			319-***					
			20				320-***					
			21,3		1/2		321.3-***	50	33	36	0,6	30
			22	7/8		3/4	322-***	1.97	1.30	1.42	.02	1.18
			25				325-***					
4	4		25,4	1			325.4-***					
			26,9		3/4		426.9-***					
			28				428-***	59	40	42	0,6	30
			28,6			1	428.6-***	2.32	1.57	1.65	.02	1.18
			30				430-***					
			32				432-***					
5	5		32	1-1/4			532-***					
			33,7		1		533.7-***					
			35			1-1/4	535-***	71	52	58	0,8	30
			38	1-1/2			538-***	2.80	2.05	2.28	.03	1.18
			40				540-***					
			41,3			1-1/2	541.3-***					
6	6		42		1-1/4		542-***					
			44,5	1-3/4			644.5-***					
			48,3		1-1/2		648.3-***	86	66	66	0,8	30
			50,8	2			650.8-***	3.39	2.60	2.60	.03	1.18
			54		2		654-***					
			57,2	2-1/4			757.2-***					
7	7		60,3		2		760.3-***					
			63,5	2-1/2			763.5-***	121	94	93	0,8	30
			70	2-3/4			770-***	4.76	3.70	3.66	.03	1.18
			73		2-1/2 (ANSI B 36-10)		773-***					
			76,1	3	2-1/2 (DIN EN 10220)		776.1-***					
			88,9		3		888.9-***	147	120	118	0,8	30
8	8		102	4	3-1/2		8102L-***	5.79	4.72	4.65	.03	1.18

Additional outside diameters are available upon request. Please contact STAUFF for further information.

Dimensional drawings: All dimensions in mm (in).

